


SIZE CHART:

Rubber mounted head												
Model	D(mm) Diameter	H(mm) Height	d(mm) Shank diameter		h/mm Shank Length	Grit Size(#)		Package (pcs/bag)	Speed of revolution (rpm)	Graph 3D drawing		
			3	6								
X03103	3	10	▪		30	60-1500	General: 60 80 120 180 240 320 400 600 Make-- to--order: 800 1500	100	25000			
X04133	4	13	▪		30							
X05153	5	15	▪		30							
X06173	6	17	▪		30							
X08203	8	20	▪		30							
X10203	10	20	▪		30							
X10206	10	20		▪	35							
X10256	10	25		▪	35							
X12203	12	20	▪		30							
X12206	12	20		▪	35							
X12256	12	25		▪	35							
X16256	16	25		▪	35							
X20033	20	3	▪		30							
X20043	20	4	▪		30							
X20053	20	5	▪		30							
X20256	20	25		▪	35			50				
X25033	25	3	▪		30			10				
X25043	25	4	▪		30							
X25053	25	5	▪		30			50				
X25256	25	25		▪	35							
X30066	30	6		▪	35			100				
X30086	30	8		▪	35							
X30106	30	10		▪	35			40				
X30256	30	25		▪	35							
X40066	40	6		▪	35			50				
X40086	40	8		▪	35							
X40106	40	10		▪	35							
Model number: HDXHXd												

Other dimensions custom please visit www.kytools.cn or send to beibei.liu@kytools.cn

DETAILED DESCRIPTION:

- ▶ **Raw material:** Alumina
- ▶ **Particle size:** 60#、80#、120#、180#、240#、320#、400#、600#、800#、1500#
- ▶ **Shape:** Cylindrical, T-shaped, conical, spherical
- ▶ **Shank diameter:** 3mm、6mm、3.175mm、6.35mm
- ▶ **Handle length:** 30mm、35mm (other sizes can be customized)
- ▶ **Hardness of grinding head:**

High elastic grinding head, adjustable hardness (customizable) This product has a variety of specifications and granularity, accept non-standard size customization, range including height, aperture, material, handle length, etc. The most prominent features of this series of products are soft polishing and fine polishing. Can cooperate with various high speed electric tools or pneumatic tools. It is mainly used



for edge honing of carbide tools to remove fine burr from various materials. And widely used to remove resin mold burn marks, scales, rust, scratches, dents and chuck marks cleaning treatment; Also suitable for removing paint, electroplating and coating, by adjusting the high elasticity of rubber material, thus preventing machining scratches.


PARTICLE SIZE GUIDE:

Particle size	60	80	120	180	240	320	400	600	800	1500
color										
	Purple	red	green	bean sauce	blue	gray	brown	light	yellow	cyan




GRANULE RUBBER MOUNTED HEAD

General information



SIZE CHART:

Granule rubber mounted head									
Model	D(mm) Diameter	H(mm) Height	d(mm) Shank diameter		h/mm Shank Length	Grit Size(#)	Package (pcs/bag)	Speed of revolution (rpm)	Graph 3D drawing
			3	6					
Z03103	3	10	▪		30	80 120 180	100	25000	
Z04133	4	13	▪		30				
Z05153	5	15	▪		30				
Z06173	6	17	▪		30				
Z08203	8	20	▪		30				
Z10203	10	20	▪		30				
Z10206	10	20		▪	35				
Z10256	10	25		▪	35				
Z12203	12	20	▪		30				
Z12206	12	20		▪	35				
Z12256	12	25		▪	35				
Z16256	16	25		▪	35				
Z20033	20	3	▪		30				
Z20043	20	4	▪		30				
Z20053	20	5	▪		30				
Z20256	20	25		▪	35		50		
Z25033	25	3	▪		30		10		
Z25043	25	4	▪		30				
Z25053	25	5	▪		30		50		
Z25256	25	25		▪	35				
Z30066	30	6		▪	35		100		
Z30086	30	8		▪	35				
Z30106	30	10		▪	35		40		
Z30256	30	25		▪	35				
Z40066	40	6		▪	35		50		
Z40086	40	8		▪	35				
Z40106	40	10		▪	35				
Model number: HDXHXd									

Other dimensions custom please visit www.kytools.cn or send to beibei.liu@kytools.cn

DETAILED DESCRIPTION:

- ▶ **Raw material:** Alumina oxide
- ▶ **Particle size:** 80#、120#、180#
- ▶ **Shape:** Cylindrical, T - shaped, conical, spherical
- ▶ **Shank diameter:** 3mm、6mm、3.175mm、6.35mm
- ▶ **Handle length:** 30mm、35mm (other sizes can be customized)
- ▶ **Hardness of grinding head:**

high elastic grinding head, adjustable hardness (customizable). This product has a variety of specifications and granularity, accept non-standard size customization, range including height, aperture, material, handle length, etc. This series of products are composed of special abrasive particles and original rubber, which is also a three-in-one polishing head for grinding, polishing and cleaning, with



the rubber wheel, the elasticity is smaller, the density is higher, the hardness is higher, more suitable for the rough, dirty metal, aluminum alloy and other surfaces for derusting, removing barbs, and welding interface and other uneven surface of the initial polishing. Efficient grinding not only burnishes a rough surface, it also does not burn parts or cause discoloration.

PARTICLE SIZE GUIDE:

Particle size	80	120	180
color	red	green	earthy yellow



KEYING

CHARACTERISTICS:

A large collection of various dental burs arranged in rows, showing different shapes, sizes, and colors (green, blue, orange, yellow, red, purple, brown, and black).



- ▶ Rubber elasticity ensures smooth polishing marks, thus addressing surface roughness and preventing deep polishing lines from occurring.
- ▶ The unique elasticity (softness) of rubber sesame prevents machining marks caused by grinding between the work piece during use to provide a fine polished surface.
- ▶ Adapt to the surface, eliminate the impact of the work-piece
- ▶ Instability. Not only can be aligned with the workpiece correctly, to achieve a stable polishing surface, but also with less work to polish. Continuous polishing, small dust index, so as to improve the operating environment, ensure safe operation.
- ▶ Fine polishing, reduce the polishing process, get the best polishing effect.

WHEEL LIFE CYCLE

Wheel Size (μm)	Initial processing of deburring and rust removal	Intermediate processing of grinding and polishing	Highly efficient grinding and cutting, idea for rust and scratch removal, deburring, welding cleaning etc.	Polishing, shinning and mirror effect
60	Yes	No	No	No
80	Yes	Yes	No	No
120	No	Yes	Yes	No
180	No	No	No	Yes
240	No	No	No	Yes
320	No	No	No	Yes
400	No	No	No	Yes
600	No	No	No	Yes
800	No	No	No	Yes
1500	No	No	No	Yes

Legend:
■ Granulee rubber mounted wheel
■ Rubber mounted wheel