

FULL/ INTERLEAVED NON-WOVEN KEY-HOLE GRINDING DRUMS

General information

The raw material of non-woven grinding drum is consistent by high quality abrasives from Italy and USA. Extremely tightly connections between individual flaps provides a high degree of abrasives materials. Enthought, It has good thermal and high performance capacity.

APPLICATIONS:

Matting, deburring, surface finishing, cleansing, fine grinding

Machine: Drum grinders

INFORMATION POINTS:

- ▶ 19mm hole with 4 keyways fits
- ▶ Raw material: AO/ SC
- ▶ Interleaved abrasive clothes grits:

AO GRIT:

60	80	100	120	150	180	240	320	400	600	800	1000	1200
----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------

SC GRIT:

60	80	100	120	150	180	240	320	400	600	800	1000	1200
----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------




TABLE:

D (mm)	H (mm)	d (mm)	Grit	Opt RPM	Max RPM	Package 
100	100	19	AC.AM.AF.AVF	2500	4000	1pcs/box
110	100	19	AC.AM.AF.AVF			
120	100	19	AC.AM.AF.AVF			
100	50	19	AC.AM.AF.AVF			
110	50	19	AC.AM.AF.AVF			

Other dimensions custom please visit www.kytools.cn or send to beibei.liu@kytools.cn

ADVANTAGES:

- ▶ Good stock removal capacity
- ▶ A high flexibility
- ▶ Good thermal capacity
- ▶ Long tool life
- ▶ Tingly packed flaps with full non-woven materials

RECOMMENDATIONS FOR USE:

Please see tables with rotational speed suggestion.

Level	Grit (#)	Abrasives
Coarse	60/80	Aluminium Oxide
Medium	100/120	
Fine	150/180	
Very Fine	240/320	
Medium	150/180	Silicon Carbide
Fine	240/320	

SAFETY NOTES:

For safety reasons, please never be exceeded the recommended speed.

