



The non-woven products range is for masking marks operations and decretive operations with stock removal capacity. They are mainly working for matte and satin-finish of a variety of workpiece surface, it finally comes out different design of surfaces structures and roughness levels which will depends on the hardness grits and abrasive tools' appearance designs.

CHARACTERS:

A high flexibility and good thermal capacity

SAFETY RECOMMENDATION:

Please see tables with rotational speed suggestion.

- ▶ Full Non-woven flap wheels
- ▶ Interleaved Non-woven flap wheels
- ▶ Non-woven flap discs
- ▶ Non-woven M14 unmounted grinding wheels
- ▶ Non-woven Key-cross grinding drum
- ▶ Self-adhesive discs
- ▶ Periclean discs

Level	Grit (#)	Abrasives
Coarse	60/80	Aluminium
Medium	100/120	
Fine	150/180	
Very Fine	240/320	
Ultra Fine	400/600	
Micro Fine	800/1000	
Medium	150/180	Oxide/Silicon
Fine	240/320	Carbide

INTERLEAVED NON-WOVEN FLAP WHEELS WITH SHANK

General information



RECOMMENDATION OF MAX. RPM:

D (mm)	Recommend RPM	Max.RPM
30	9600	20300
40	7500	15200
50	5700	12200
60	4700	10100
75	4000	7000
80	4000	7000
100	3600	5700




TABLE:

Production code	Diameter (mm)	Height (mm)	Handle length (mm)	Shank Diameter (mm)		Grit Size	Package 	The highest speed (rpm)	
				3	6				
INW30156	30	15	35		●	AC C M F VF UF SUF	150pcs/bag	19000	
INW30206	30	20			●				
INW30256	30	25			●				
INW30306	30	30			●				
INW40156	40	15			●		100pcs/bag	14000	
INW40206	40	20			●				
INW40256	40	25			●				
INW40306	40	30			●				
INW40406	40	40			●		70pcs/bag	11500	
INW40506	40	50			●				
INW50156	50	15			●				
INW50206	50	20			●				
INW50256	50	25			●		50pcs/bag	9500	
INW50306	50	30			●				
INW50406	50	40			●				
INW50506	50	50			●				
INW60156	60	15			●		30pcs/bag	7000	
INW60206	60	20			●				
INW60256	60	25			●				
INW60306	60	30			●				
INW60406	60	40			●		18pcs/bag		
INW60506	60	50			●				
INW80156	80	15			●				
INW80206	80	20			●				
INW80256	80	25			●				
INW80306	80	30			●				
INW80406	80	40			●				
INW80506	80	50			●				

Other dimensions custom please visit www.kytools.cn or send to beibei.liu@kytools.cn